

wood rubberTM

rubberised sealer

Email: info@ecorubber.co.za

Neil : 076 141 5138

Marius: 083 262 6432

Website: www.ecorubber.co.za

ECO WOOD

PRODUCT DESCRIPTION	<ul style="list-style-type: none"> * Eco Wood is a waterproofing protective and decorative coating, formulated on an elastomeric polymer base. * This water-borne coating boast with cutting edge technology where the formulation is highly UV resistant. * Eco Wood provides superior adhesion that proof to resist weathering, chalking and cracking. * This product create a waterproofing membrane barrier that is UV reflective. * The external coating proofs to show significant reduction in colour fading due to the oxide colouring technology that is applied.
----------------------------	---

PRODUCT BENEFITS	<ul style="list-style-type: none"> * Improves life span of substrates that were coated * Waterproofing at it's best!! * Stretchable and contract to its original form, therefore with standing thermal cycling. * No solvents, there for it is Environmentally Friendly and can be applied were rainwater is harvested. * No negative effect on human or animal life. * Waterproofing that can with stand ponding. * Spray, paint or roller applied * Total ambient temperature application. required.
-------------------------	--

MATERIAL APPLICATION

SURFACE PREPARATION	<ul style="list-style-type: none"> * Surfaces to be sprayed / painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign materials. Allow all surfaces to dry completely prior to painting. * Avoid application when the moisture is above 15% * Remove all unstable paint film. * Repair defected surfaces before application.
MATERIAL	Single component, ready-to-use from container with little stirring required.
APPROXIMATE COVERAGE	1 kg per square meter, will cure to 850 micron membrane.
APPLICATION TEMPERATURE RANGE	Above 10°C
RECOATING	Excellent
PRIMARY CURE	3 hours at 25°C
FINAL CURE TIME	3 - 5 Days
AIRLESS SPRAY	Pressure : 1600 - 1700 psi
THINNER (VOLUME)	Must NOT be thinned

TECHNICAL DATA

PARAMETER	Pure Acrylic Polymer
FINISH	Homogeneous: smooth, various colours
SELF PRIMER	Positive
PH	8.61
VISCOSITY	109 ku
SPECIFIC GRAVITY	1.299
TOXICITY	Material is non-toxic & requires no special ventilation during application. Contains no materials considered to be health hazards.
FLAMMABILITY	Non-flammable. Does not support flame spread. Class 3
PACKAGE STABILITY	One year + after opening: no settling or other undesirable effects. Materials
ABRASION RESISTANCE	Medium to High. Suitable for high foot traffic areas
ELONGATION	50% with a 100% full memory
FUNGUS RESISTANCE	No fungus growth when material tested in an environment of three organisms.
V.O.C	78 grams per Litre
WATER, %	9%
SOLIDS BY MASS	58%
TSC	62%
FISH EYE TEST	Non - Passed
FILM HARDNESS	Flexible
FLASH POINT	Water borne - not flammable
FIRE INDEX	Class 3
CHEMICAL RESISTANCE	Resistant to common acids and alkaline spills at medium to high concentrations.
UV RESISTANCE	Will start to degrade after 7 - 10 + years

STANDARD PACKAGING

PACKAGING	2.5 kg / 5 kg
------------------	---------------

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none">* Keep container tightly closed and keep out of reach of children or away from food and drink.* In case of contact with eye, rinse with plenty of water immediately and seek medical advice.* Remove splashes from skin by using soap or water.* Always keep container in a secure upright position.* Dispose off any paint waste in accordance with the appropriate EHS Regulations
---------------------------	--

NOTE: We warranty only the quality of our product and the data sheet is based on results obtained from experience and tests.

We reserve the right to change data without prior notice.

